



VIN-IP-3PTZ-256-IWF 3MP WiFi Mini Pan Tilt ATC Camera

- 3mp (2304x1296) Resolution
All time color vision
- Full duplex audio intercom (Built-in high sensitive Mic & Speaker)
- Horizontal resolution: 350, Vertical Resolution: 90
- Support 10x digital zoom
10 Preset points for favorite location
- Smart human detection, Motion detection, Motion tracking
- Mobile notification on human & motion detection
Customized Pre-recorded voice alarm
- Support Micro-SD card upto 256GB & cloud storage(Opt.)
- ONVIF supported
- QR Code scanning for network connection
- Monitoring: Mobile/PC Software (EseeCloud)
- Ip66 Waterproof Rating, 4K Lighting protection
- Alexa support



Feature	Specification
Image Sensor	1/3" CMOS Sensor
Resolution	3MP (2304x1296)
Video Compression Standard	H.264+ / H.265 / H.265+
Lens	4mm
IR LED	6 IR LED's
Infrared IR Distance	30 Meters
White LED	6 White Array LED's
White IR Distance	20 Meters
Light Mode	Full color / Infrared
Minimum Illumination	Color : 0.01Lux, Black and White : 0.001 Lux
Video Streaming	Main stream : 2304x1296 / 15FPS; Substream: 640 x 360 / 15FPS
PTZ Rotation Range	Horizontal 350° 0.1°~20°/sec, Vertical 90° 0.1°-20°/sec;
Audio Input / Output	Supports two-way audio, built-in microphone and speaker
Audio Compression Standard	AAC / G711A
Protocol	N1/ONVIF
Connectors	Rj45 LAN Connectors (100 Mbps) and DC Power Input
Zoom	10X Digital Zoom
Light Mode	Full Color / Infrared / Intelligent
Alarm	1) Motion Detection, Alarm Picture Push 2) Human Detection, Alarm Picture Push
DNR	3D Digital Noise Reduction

*Product casing and specifications are subject to change without prior notice..



Day & Night	IR Cut Auto ICR
Min Illumination	Color: 0.01Lux, Black & White: 0.001 Lux
White Balance	Auto
WDR	D-WDR
Micro / Flip	On / Off
Electronic Shutter	Auto
Connection Mode	WiFi (IEEE802.11b/g/n) Network
Video Tuning	Contrast, Brightness, Saturation, Sharpness Adjustment
On Screen Display	Date, Time & Title
AI Features	Motion Detection, Human Detection, Human Detection
Privacy Zone	Support 4 Zone
Monitoring	Android, iOS, Windows (EseeCloud)
Slots	Micro SD Card
Storage	Support Micro SD Card upto 256GB & Cloud Storage (Optional)
Button	Reset
Light Mode Indication	LED Blink: Not Connected to Network, LED Continuous ON: Connected to Network
Power Input	DC: 12V/1A (DC 2.1mm Connector)
Power Consumption	15W
Thunder Prevention	Standard IEC61000-4-5
Working Temperature/Humidity	0-50 C RH Less Than 95% (No Condensation)
Storage Temperature/Humidity	-20 C to 60 C / 20% to 90% RH
Housing Type	Plastic IP66
Dimension	191mm x 132mm x 170mm (H x W x L)
Net Weight	550 Gms
Gross Weight	800 Gms

